

Amendments to the Claims

✓ The listing of claims below will replace all prior versions and listings of claims in the present application.

Claim Listing

1 1. (Original) A source synchronous clocking system, comprising:  
 2 a source clock domain in a first layer, comprising:  
 3 a register having a first input for receiving a data signal, a second input for  
 4 receiving a clock signal, and an output; and  
 5 a buffer having an input for receiving the clock signal and an output, said  
 6 buffer generating a delay that is substantially equivalent to a delay  
 7 through said register; and  
 8 a destination clock domain in a second layer, comprising:  
 9 a register having a first input and a second input, the first input of said  
 10 register of said destination clock domain being coupled to the  
 11 output of said register in the source clock domain.

1 2. (Original) The source synchronous clocking system of Claim 1 wherein said  
 2 source clock domain comprises a first transmit clock domain in the first layer for  
 3 transmitting the data and clock signals to the said destination clock domain that  
 4 comprises a transmit clock domain in the second layer, said first layer comprising a link  
 5 layer, said second layer comprising a PHY layer.

1 3. (Original) The source synchronous clocking system of Claim 1 wherein said  
 2 source clock domain comprises a first receive domain said the first layer for transmitting  
 3 data and clock signals to said destination clock that comprises a receive clock domain in  
 4 said second layer, said first layer including a PHY layer, said second layer including a  
 5 link layer.

1 4. (Original) The source synchronous clocking system of Claim 1 further  
 2 comprising a delay circuit, coupled between said source clock domain and said  
 3 destination clock domain, for introducing additional delay to the clock signal.

1 5. (Original) The source synchronous clocking system of Claim 1 further  
 2 comprising a second buffer having an input coupled to the output of said delay circuit and  
 3 an output coupled to said register in said destination clock domain.

1 6. (Original) The source synchronous clocking system of Claim 1 further  
 2 comprising a serial termination circuit for absorbing a reflection generated by the data  
 3 signal.

1 7. (Original) The source synchronous clocking system of Claim 1 further  
 2 comprising a parallel termination circuit for absorbing a reflection generated by the data  
 3 signal.

1 8. (Original) The source synchronous clocking system of Claim 5 wherein the  
 2 clock signal generated from the output of the second buffer being connected to a clock  
 3 input of in said destination clock domain.

1 9. (Currently Amended) A method for operating a source synchronous clocking  
 2 system between a first layer and a second layer from a source clock, comprising:  
 3 receiving an input clock signal in a first clock domain in a first layer;  
 4 receiving an input data signal in the first clock domain in the first layer;  
 5 ~~sourcing the input clock signal and the input data signal from a source clock, the~~  
 6 ~~source clock triggering the input clock signal and the input data signal;~~  
 7 and  
 8 latching the input data signal by triggering the input data signal by the input clock  
 9 signal;  
 10 delaying the input clock signal by an amount that is equal to the delay in the  
 11 latching; and

12 generating an output clock signal and an output data signal in the second clock  
13 domain in the second layer, the output clock signal and the output data  
14 signal being synchronized to each other.

1 10. (Original) The method of Claim 9 wherein the first layer comprises a link  
2 layer and the second layer comprises a PHY layer, the input clock and data signal being  
3 transferred from the link layer to the link layer.

1 11. (Original) The method of Claim 9 wherein the first layer comprises a PHY  
2 layer and the second layer comprises a link layer, the input clock and data signal being  
3 transferred from the PHY layer to the link layer.

12. (Cancelled)

13. (Cancelled)

1 14. (Currently Amended) A method for ~~sourcing~~ providing a clock input and a  
2 data input synchronously between a link layer and a PHY layer, the link layer including a  
3 transmit clock domain and a receive clock domain, the PHY layer including a transmit  
4 clock domain and a receive clock domain, comprising the steps of:  
5 receiving the clock input;  
6 receiving the data input;  
7 transmitting the clock input to a latching device for triggering the data input;  
8 sending the clock input through a buffer, the buffer having a delay which is equal  
9 to the delay through the latching device; and  
10 generating an output data from the latching device that synchronizes with an  
11 output clock from the buffer.

1 15. (Original) The method of Claim 14 wherein the transmitting step comprises  
2 transmitting the clock input from a link layer to a PHY layer.

1 16. (Original) The method of Claim 14 wherein the transmitting step comprises  
2 transmitting the clock input from a PHY layer to a link layer.

1 17. (Original) The method of Claim 14 further comprising the step of merging  
2 the clock signal at the PHY layer to a clock input at the PHY layer.

1 18. (Original) The method of Claim 14 further comprising the step of absorbing  
2 the reflection generated from the data input by serial termination.

1 19. (Original) The method of Claim 14 further comprising the step of absorbing  
2 the reflection generated from the data input by parallel termination.

1 20. (Original) The method of Claim 14 further comprising generating control  
2 signals of the data input, the control signals being multiplexed with the data input.

---

*For  
Amend.*